



- 80 PLUS[®] Gold certified efficiency
- Fully modular cable management
- Full-bridge LLC converter with DC-to-DC technology
- Low ripple and tight voltage regulation
- 5-year warranty

With the **PowerUp series**, **Chieftronic** aims to bring the well-received technical quality and high performance of the PowerPlay series to the mainstream gamer's market. With modern full-bridge LLC and DC-to-DC technology, extremely low ripple values and tight voltage regulation can be achieved.

A high power-density design allows this series to deliver up to 850W of power in a compact form factor, measuring only 14 cm in total length, while achieving **80 PLUS® Gold certified efficiency**. The compact size combined with the fully modular cable management, allows the PowerUp series to be used conveniently in smaller builds, where a short PSU is needed, while long, flat, black cables support builds even in very large gaming cases.





Technical data				
Model	PowerUp 850W			
Article no.	GPX-850FC			
ATX 12V version	V2.53			
Efficiency	80 PLUS® Gold			
PFC	Active PFC			
Fan	120mm silent fan			
Dimension (DxWxH)	140mm x 150mm x 86mm			
Security	AFC (Automatic Fanspeed Control) OCP (Over Current Protection) OPP (Over Power Protection) OTP (Over Temperature Protection) OVP (Over Voltage Protection) SCP (Short-Circuit Protection) SIP (Surge & Inrush Protection) UVP (Undervoltage Protection)			
Warranty	60 months			

Output data								
	AC Input	100-240V / 47 - 63Hz / 12.0A						
PowerUp 850W	DC Output	+3.3V	+5V	+12V	-12V	+5VSB		
	Max. Current	20.0A	20.0A	70.5	0.3A	2.5A		
	Max. Combined Power	110W		846W	3.6W	12.5W		
				850W				

* The listed specifications may be altered at any point in time without any pre-notice.

** Chieftronic® is a registered trademark. All other brands and/or logos are property of the respective owners.

Arena Electronic GmbH Koppersstr. 18, 40549 Düsseldorf Germany Tel. +49(0)211 91 31 51 - 0 Fax. +49(0)211 91 31 51 - 99 Email: info@chieftronic.com



PowerUp Series | 850W

Cable	Connectors	Length (mm)	
24 PIN ATX	1	650	
8 PIN PCIe (6+2)	6	3x 500/150	
8 PIN CPU (4+4)	2	650/150	
SATA	9	3x 500/150/150	
Molex	3	500/150/150/150	
Floppy	1	500/150/150/150	

 CECB Effication

 Image: Certification

 Image: Certification

Version: 11/2020

* The listed specifications may be altered at any point in time without any pre-notice.

** Chieftronic® is a registered trademark. All other brands and/or logos are property of the respective owners.

Arena Electronic GmbH Koppersstr. 18, 40549 Düsseldorf Germany Tel. +49(0)211 91 31 51 - 0 Fax. +49(0)211 91 31 51 - 99 Email: info@chieftronic.com