

POWER UP



FEATURES

80 PLUS Gold Certified : This certification guarantees a typical efficiency of 90% under normal operating conditions.

Performance Driven Topology : The half-bridge LLC resonant converter and DC-DC technology offer reliable and stable voltage outputs for safer, more reliable performance and higher efficiency.

Semi-Fanless Mode with Hybrid Switch: The 135mm FDB fan is semi-fanless up to 40% load and can be manually turned off with a hardware based hybrid switch.

Full-Modular Cabling : Modular cables reduce clutter, increase airflow, and improve overall efficiency and thermal performance.

16 AWG PCI-e Cables : The thicker 16 AWG PCI-e cables allow for higher currents, thereby improving both efficiency and safety.

10 Year Warranty : This unit comes with a standard limited manufacturing warranty of 10 years from the date of purchase.

PACKAGE INFORMATION

EAN	UPC
4719512068588	884102041099
4719512068595	884102041105
4719512068564	884102041075
4719512068625	884102041136
4719512068601	884102041112
4719512068571	884102041082
4719512068694	884102041204
4719512068557	884102041068
4719512068540	884102041051
	4719512068588 4719512068595 4719512068564 4719512068625 4719512068601 4719512068571 4719512068694 4719512068557

Nett Weight	1.82 kg / 4.012 lb
Gross Weight	2.35 kg / 5.181 lb
Package Dimensions	303 x 202 x 125mm (11.93 x 7.95 x 4.92")
Carton Dimensions	520 x 318 x 238mm (20.47 x 12.52 x 9.37")
Unit / Carton	4 pcs
Carton / Pallet	24 pcs

The V Gold - v2 offers the high quality user experience you've always wanted. Enjoy an 80 Plus Gold efficiency rating, full-modular cabling, semi-fanless operation, a 135mm FDB fan, 16AWG PCIe high efficiency cables, and a 10 year warranty. Improvements and innovations from the components to the cables deliver a power supply unit fit for any and every type of PC. The 100% Japanese capacitors, half-bridge LLC resonant convertor, and DC-DC circuitry deliver a product that even the pros can respect, at 550, 650, 750, and 850 watt levels. Also available with black casing and cables.

SPECIFICATIONS

Product Name	e	V550 Gold - v2 (White Edition)			
Item Code		MPY-550V-AGBAG			
ATX Version		ATX 12V Ver. 2.52			
PFC		Active PFC			
Input Voltage		100-240V			
Input Current		8-4A			
Input Frequency		50-60Hz			
Dimensions (L x W x H)		160 x 150 x 86mm			
Fan Size		135mm			
Fan Bearing		FDB			
Fan Speed		1161 RPM			
Noise @ 20%		0 dBA			
Noise @ 50%		18.3 dBA			
Noise @ 100%	6	24.9 dBA			
Efficiency		90% @ Typical Load			
80 PLUS Rating		80 PLUS Gold			
ErP 2014 Lot 3		Yes			
Operating Temperature		0~50°C			
Power Good Signal		100-500ms			
Hold Up Time		17ms			
MTBF		>100,000 hours			
Protections		OVP / OPP / SCP / OCP / UVP / OTP			
Regulatory		CCC, CE, TUV-RH, RCM, EAC, cTUVus,			
		FCC, BSMI, KC, CB			
Connectors	ATX 24 Pin	x1			
	EPS 4+4 Pin	x1			
	EPS 8 Pin	x1			
	SATA	x8			
	Peripheral 4 Pin	x4			
	FDD	x0			
	PCI-e 6+2 Pin	x2			

AC INPUT	100-240V~ 8-4A 50-60Hz				
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5Vstb
	20A	20A	45A	0.3A	3A
TOTAL POWER	130W		540W	3.6W	15W
	550W				

FEATURES




This certification guarantees a typical efficiency of 90% under normal operating conditions.



The half-bridge LLC resonant converter and DC-DC technology offer reliable and stable voltage outputs for safer, more reliable performance and higher efficiency.



The 135mm FDB fan is semi-fanless up to 40% load and can be manually turned off with a hardware based hybrid switch.



Modular cables reduce clutter, increase airflow, and improve overall efficiency and thermal performance.



The thicker 16 AWG PCI-e cables allow for higher currents, thereby improving both efficiency and safety.



This unit comes with a standard limited manufacturing warranty of 10 years from the date of purchase.