







SPECIFICATIONS

Panel Resolution3440 x 1440 (UWQHD)Refresh Rate100HzResponse timeIms(MPRT)DYNAMIC REFRESH RATE TECHNOLOGYAdaptive-SyncPanel TypeVABrightness (nits)250Viewing Angle178°(H) / 178°(V)Aspect Ratio21:9Curvature1500RContrast Ratio3000:1DCR10000000:1Pixel Pitch (H x V)0.23175(H) x 0.23175 (V)Surface TreatmentAnti-glareDisplay Colors16.7MDCI-P3 / sRGB89.48% / 112.2%Video ports1 x Earphone outKensington LockYesVESA Mounting75 x 75 mmPower TypeExternal Adaptor 19V 3.42APower Input100~240V, 50~60HzSignal Frequency58.56 to 148.1KHz(H) 48 to 1004z(V)Adjustment (Tilt)-5° ~ 5°Adjustment (Tilt)-5° ~ 5°Adjustment (Height)0 -90mmDimension (W x H x D)810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inchGarton Dimension (W X H X D)910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inchWeight (NW / GW)6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbsFrameless DesignYes	Panel Size	34" (86.36 cm)
Response timeIms(MPRT)DYNAMIC REFRESH RATE TECHNOLOGYAdaptive-SyncPanel TypeVABrightness (nits)250Viewing Angle $178^{\circ}(H) / 178^{\circ}(V)$ Aspect Ratio21:9Curvature1500RContrast Ratio3000:1DCR100000000:1Pixel Pitch (H x V)0.23175(H) x 0.23175 (V)Surface TreatmentAnti-glareDisplay Colors16.7MDCI-P3 / sRGB89.48% / 112.2%Video ports1 x Earphone outKensington LockYesVESA Mounting75 x 75 mmPower TypeExternal Adaptor 19V 3.42APower Input100~240V, 50~60HzSignal Frequency58.56 to 148.1KHz(H) 48 to 100Hz(V)Adjustment (Tilt)-5° ~ 20°Adjustment (Pivot)-5° ~ 5°Adjustment (Height)0 - 90mmDimension (W x H x D)910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inchWeight (NW / GW)6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Panel Resolution	3440 x 1440 (UWQHD)
DYNAMIC REFRESH RATE TECHNOLOGYAdaptive-SyncPanel TypeVABrightness (nits)250Viewing Angle $178^{\circ}(H) / 178^{\circ}(V)$ Aspect Ratio21:9Curvature1500RContrast Ratio3000:1DCR100000000:1Pixel Pitch (H x V)0.23175(H) x 0.23175 (V)Surface TreatmentAnti-glareDisplay Colors16.7MDCI-P3 / sRGB89.48% / 112.2%Video ports1 x DP (1.2)1 x HDMI (2.0) 1 x HDMI (2.0) 1 x HDMI (2.4)Audio ports1 x Earphone outKensington LockYesVESA Mounting75 x 75 mmPower TypeExternal Adaptor 19V 3.42APower Input100~240V, 50~60HzSignal Frequency58.56 to 148.1KHz(H) 48 to 100Hz(V)Adjustment (Tilt)-5° ~ 5°Adjustment (Fivot)-5° ~ 5°Adjustment (Height)0 - 90mmDimension (W x H x D) $910 \times 210 \times 485 \text{ mm} / 35.83 \times 8.27 \times 19.09 \text{ inch}Weight (NW / GW)6.91 \text{ kg} / 9.36 \text{ kg} / 5.24 \text{ lbs} / 20.64 \text{ lbs}$	Refresh Rate	100Hz
TECHNOLOGYAdaptive-SyncPanel TypeVABrightness (nits)250Viewing Angle178°(H) / 178°(V)Aspect Ratio21:9Curvature1500RContrast Ratio3000:1DCR100000000:1Pixel Pitch (H x V)0.23175(H) x 0.23175 (V)Surface TreatmentAnti-glareDisplay Colors16.7MDCI-P3 / sRGB89.48% / 112.2%Video ports1 x DP (1.2)1 x HDMI (2.0)1 x HDMI (2.0)1 x HDMI (2.0)1 x HDMI (2.0)1 x HDMI (1.4)Audio ports1 x Earphone outKensington LockYesVESA Mounting75 x 75 mmPower TypeExternal Adaptor 19V 3.42APower Input100~240V, 50~60HzSignal Frequency58.56 to 148.1KHz(H) 48 to 100Hz(V)Adjustment (Tilt)-5° ~ 5°Adjustment (Rivel)-30° ~ 30°Adjustment (Height)0 - 90mmDimension (W x H x D)910 x 210 x 485 mm / 31.89 x 10.63 x 20.08 inchCarton Dimension (W X H X D)910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inchWeight (NW / GW)6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Response time	1ms(MPRT)
Brightness (nits) 250 Viewing Angle 178°(H) / 178°(V) Aspect Ratio 21:9 Curvature 1500R Contrast Ratio 3000:1 DCR 100000000:1 Pixel Pitch (H x V) 0.23175(H) x 0.23175 (V) Surface Treatment Anti-glare Display Colors 16.7M DCI-P3 / sRGB 89.48% / 112.2% Video ports 1 x DP (1.2) 1 x HDMI (2.0) 1 x HDMI (2.0) 1 x HDMI (2.0) 1 x HDMI (2.0) 1 x HDMI (1.4) Audio ports Audio ports 1 x Earphone out Kensington Lock Yes VESA Mounting 75 x 75 mm Power Input 100~240V, 50~60Hz Signal Frequency 58.56 to 148.1KHz(H) 48 to 100Hz(V) Adjustment (Tilt) -5° ~ 20° Adjustment (Fivot) -5° ~ 5° Adjustment (Height) 0 - 90mm 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W x H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW)		Adaptive-Sync
Viewing Angle 178°(H) / 178°(V) Aspect Ratio 21:9 Curvature 1500R Contrast Ratio 3000:1 DCR 100000000:1 Pixel Pitch (H x V) 0.23175(H) x 0.23175 (V) Surface Treatment Anti-glare Display Colors 16.7M DCI-P3 / sRGB 89.48% / 112.2% Video ports 1 x Earphone out Kensington Lock Yes VESA Mounting 75 x 75 mm Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Signal Frequency 58.56 to 148.1KHz(H) 48 to 100Hz(V) Adjustment (Tilt) -5° ~ 5° Adjustment (Fivot) -5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Panel Type	VA
Aspect Ratio 21:9 Curvature 1500R Contrast Ratio 3000:1 DCR 100000000:1 Pixel Pitch (H x V) 0.23175(H) x 0.23175 (V) Surface Treatment Anti-glare Display Colors 16.7M DCI-P3 / sRGB 89.48% / 112.2% Video ports 1x DP (1.2) 1x HDMI (2.0) 1x HDMI (2.0) 1x HDMI (1.4) Audio ports Audio ports 1 x Earphone out Kensington Lock Yes VESA Mounting 75 x 75 mm Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Signal Frequency 58.56 to 148.1KHz(H) Adjustment (Tilt) -5° ~ 20° Adjustment (Fivot) -5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 910 x 210 x 485 mm / 33.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Brightness (nits)	250
Curvature 1500R Contrast Ratio 3000:1 DCR 100000000:1 Pixel Pitch (H x V) 0.23175 (H) x 0.23175 (V) Surface Treatment Anti-glare Display Colors 16.7M DCI-P3 / sRGB 89.48% / 112.2% Video ports 1x DP (1.2) X HDMI (2.0) 1x HDMI (1.4) Audio ports 1 x Earphone out Kensington Lock Yes VESA Mounting 75 x 75 mm Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Signal Frequency 58.56 to 148.1KHz(H) 48 to 100Hz(V) Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Quest (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Viewing Angle	178°(H) / 178°(V)
Contrast Ratio 3000:1 DCR 10000000:1 Pixel Pitch (H x V) 0.23175(H) x 0.23175 (V) Surface Treatment Anti-glare Display Colors 16.7M DCI-P3 / sRGB 89.48% / 112.2% Video ports 1x DP (1.2) 1x HDMI (2.0) 1x HDMI (1.4) Audio ports 1 x Earphone out Kensington Lock Yes VESA Mounting 75 x 75 mm Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Signal Frequency 58.56 to 148.1KHz(H) Adjustment (Tilt) -5° ~ 20° Adjustment (Fivot) -5° ~ 5° Adjustment (Pivot) -5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Aspect Ratio	21:9
DCR 10000000:1 Pixel Pitch (H x V) 0.23175(H) x 0.23175 (V) Surface Treatment Anti-glare Display Colors 16.7M DCI-P3 / sRGB 89.48% / 112.2% Video ports 1x DP (1.2) X HDMI (2.0) 1x HDMI (2.0) 1x HDMI (1.4) Audio ports Audio ports 1 x Earphone out Kensington Lock Yes VESA Mounting 75 x 75 mm Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Signal Frequency 58.56 to 148.1KHz(H) Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) 5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Curvature	1500R
Pixel Pitch (H x V) $0.23175(H) \times 0.23175(V)$ Surface TreatmentAnti-glareDisplay Colors $16.7M$ DCI-P3 / sRGB $89.48\% / 112.2\%$ Video ports $1x DP (1.2)$ Video ports $1x HDMI (2.0)$ $1x HDMI (1.4)$ Audio ports $1 x Earphone out$ Kensington LockYesVESA Mounting $75 \times 75 mm$ Power TypeExternal Adaptor 19V 3.42APower Input $100~240V, 50~60Hz$ Signal Frequency $58.56 to 148.1KHz(H)$ Adjustment (Tilt) $-5^{\circ} \sim 20^{\circ}$ Adjustment (Pivot) $-5^{\circ} \sim 5^{\circ}$ Adjustment (Height) $0 - 90mm$ Dimension (W x H x D) $810 \times 270 \times 510 mm / 31.89 \times 10.63 x 20.08 inch$ Weight (NW / GW) $6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs$	Contrast Ratio	3000:1
Surface TreatmentAnti-glareDisplay Colors16.7MDCI-P3 / sRGB89.48% / 112.2%Video ports1x DP (1.2)1x HDMI (2.0)1x HDMI (2.0)1x HDMI (1.4)Audio ports1 x Earphone outKensington LockYesVESA Mounting75 x 75 mmPower TypeExternal Adaptor 19V 3.42APower Input100~240V, 50~60HzSignal Frequency58.56 to 148.1KHz(H)Adjustment (Tilt)-5° ~ 20°Adjustment (Swivel)-30° ~ 30°Adjustment (Height)0 - 90mmDimension (W x H x D)810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inchCarton Dimension (W X H X D)910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inchWeight (NW / GW)6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	DCR	10000000:1
Display Colors 16.7M DCI-P3 / sRGB 89.48% / 112.2% Video ports 1x DP (1.2) X HDMI (2.0) 1x HDMI (2.0) 1x HDMI (1.4) Audio ports Audio ports 1 x Earphone out Kensington Lock Yes VESA Mounting 75 x 75 mm Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Signal Frequency 58.56 to 148.1KHz(H) Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Pixel Pitch (H x V)	0.23175(H) x 0.23175 (V)
DCI-P3 / sRGB 89.48% / 112.2% Video ports 1x DP (1.2) 1x HDMI (2.0) 1x HDMI (1.4) Audio ports 1 x Earphone out Kensington Lock Yes VESA Mounting 75 x 75 mm Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Signal Frequency 58.56 to 148.1KHz(H) 48 to 100Hz(V) Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Surface Treatment	Anti-glare
1x DP (1.2) 1x HDMI (2.0) 1x HDMI (1.4) Audio ports 1 x Earphone out Kensington Lock Yes VESA Mounting 75 x 75 mm Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Signal Frequency 58.56 to 148.1KHz(H) Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 910 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Display Colors	16.7M
Video ports 1x HDMI (2.0) 1x HDMI (1.4) Audio ports 1 x Earphone out Kensington Lock Yes VESA Mounting 75 x 75 mm Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Signal Frequency 58.56 to 148.1KHz(H) 48 to 100Hz(V) Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	DCI-P3 / sRGB	89.48% / 112.2%
Kensington Lock Yes VESA Mounting 75 x 75 mm Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Signal Frequency 58.56 to 148.1KHz(H) 48 to 100Hz(V) Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Video ports	1x HDMI (2.0)
VESA Mounting 75 x 75 mm Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Signal Frequency 58.56 to 148.1KHz(H) 48 to 100Hz(V) Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Audio ports	1 x Earphone out
Power Type External Adaptor 19V 3.42A Power Input 100~240V, 50~60Hz Signal Frequency 58.56 to 148.1KHz(H) 48 to 100Hz(V) Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Kensington Lock	Yes
Power Input 100~240V, 50~60Hz Signal Frequency 58.56 to 148.1KHz(H) 48 to 100Hz(V) Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	VESA Mounting	75 x 75 mm
Signal Frequency 58.56 to 148.1KHz(H) 48 to 100Hz(V) Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Power Type	External Adaptor 19V 3.42A
Signal Frequency 48 to 100Hz(V) Adjustment (Tilt) -5° ~ 20° Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Power Input	100~240V, 50~60Hz
Adjustment (Swivel) -30° ~ 30° Adjustment (Pivot) -5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Signal Frequency	
Adjustment (Pivot) -5° ~ 5° Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Adjustment (Tilt)	-5° ~ 20°
Adjustment (Height) 0 - 90mm Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Adjustment (Swivel)	-30° ~ 30°
Dimension (W x H x D) 810 x 270 x 510 mm / 31.89 x 10.63 x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Adjustment (Pivot)	-5° ~ 5°
Dimension (W x H x D) x 20.08 inch Carton Dimension (W X H X D) 910 x 210 x 485 mm / 35.83 x 8.27 x 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Adjustment (Height)	0 - 90mm
Carton Dimension (W X H X D) 19.09 inch Weight (NW / GW) 6.91 kg / 9.36 kg 15.24 lbs / 20.64 lbs	Dimension (W x H x D)	· · · · · · · · · · · ·
15.24 lbs / 20.64 lbs	Carton Dimension (W X H X D)	· · · · · · · · · ·
Frameless Design Yes	Weight (NW / GW)	
	Frameless Design	Yes

FEATURES



UWQHD with Ultra-Wide Display Optimize your gaming experience & see every detail in crystal clarity with 21:9 UWQHD (3440 x 1440) resolution.



100Hz High Refresh Rate

100_{Hz} Experience smooth gaming with a blazing fast 100Hz refresh rate, that gives you the upperhand in fast moving games.

Mystic Light

© 79571C Make your build look on fire or cold as ice. You are in control. Customize colors and effects with RGB LED.

Wide Color Gamut

Wide Color Game colors and details will look more realistic and refined, to Gamut push game immersion to its limits.

Curved Gaming™

🕅 msi AMIN

311/2

CURVED[™] View more of your game. MSI Curved Gaming[™] monitors are perfect for gamers to play their games.

1ms Fast Response Time



Eliminate screen tearing and choppy frame rates with 1ms response time.



MONITOR

Optix MAG342CQRV SEE BEYOND THE GAME. VISUALIZE YOUR VICTORY.

Compatibility	PC, Mac, PS5 [™] , PS4 [™] , Xbox, Mobile, Notebook * All trademarks and the registered trademarks are the property of their respective owners.
Note	Display Port: 3440 x 1440 (Up to 100Hz) HDMI: 3440 x 1440 (Up to 100Hz) sRGB and DCI-P3 follow CIE1976 standrard

CONNECTIONS



- 1. 1x HDMI 1.4
- 2.1x HDMI 2.0
- 3. 1x Display Port 1.2a
- 4. 1x DC Jack
- 5. 1x Earphone out
- 6.

