




SPECIFICATIONS

Modèle	GeForce RTX™ 4080 SUPER 16G GAMING X SLIM WHITE
Processeur graphique	NVIDIA® GeForce RTX™ 4080 SUPER
Cœurs	10240 unités
Mémoire	16 Go GDDR6X
Bus Mémoire	256-bit
Fréquence du GPU	Extreme Performance : 2625 MHz (MSI Center) Boost : 2610 MHz (modes GAMING et SILENT)
Vitesse mémoire	23 Gb/s
Nombre d'écrans supportés	4
Technologie G-SYNC™	Oui
Résolution numérique maximum	7680 x 4320
Support du procédé HDCP	Oui
Bloc d'alimentation recommandé	850 watts (Min.750 watts)
Connecteurs alimentation	1 x 16 broches
Sorties	2 x DisplayPort (v1.4a) 2 x HDMI™ (Support 4K @ 120 Hz HDR, 8K @ 60 Hz HDR et de la fréquence de rafraîchissement variable telle que spécifiée par la norme HDMI™ 2.1a)
Version OpenGL	4.6
Dimensions	322 x 136 x 62 mm
Poids	1628 g (net) / 2327 g (brut)

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES

TRI FROZR 3



Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.

TORX FAN 5.0



Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.

Copper Baseplate



Heat from the GPU and memory modules is captured by a copper baseplate and then rapidly transferred to Core Pipes.

Core Pipe



Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.

Airflow Control



Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.

Metal Backplate



A sturdy backplate helps to strengthen the graphics card while a flow-through design reduces trapped heat.

Dual BIOS



Dual BIOS lets you set the priority to full performance in GAMING mode or low noise in SILENT mode.

MSI Center



The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.