

PALIT® GEFORCE RTX™ 4080 SUPER



GAMINGPRO

- ❑ One Two SYNC
- ❑ Gale Hunter Fan
- ❑ Y Formula Fins
- ❑ Ultra-Wide Copper Base
- ❑ Anti-Gravity Plate
- ❑ Exquisite Metal Backplate
- ❑ 0-dB Technology



Plug and party. Shine in consistency.

Excellent compatibility guaranteed. No need of any software control, the board lighting can be easily synced with any other ARGB-supported devices with just a single cable.



Key Features

- ❑ Dedicated Ray Tracing Cores
- ❑ Dedicated Tensor Cores
- ❑ NVIDIA DLSS 3
- ❑ Game Ready and NVIDIA Studio Drivers
- ❑ NVIDIA® GeForce Experience™
- ❑ NVIDIA Broadcast
- ❑ NVIDIA G-SYNC®
- ❑ NVIDIA GPU Boost™
- ❑ GDDR6X Graphics Memory
- ❑ PCI Express® Gen 4
- ❑ Microsoft DirectX® 12 Ultimate
- ❑ Vulkan RT APIs, Vulkan 1.3, OpenGL 4.6
- ❑ HDCP 2.3
- ❑ DisplayPort 1.4a, up to 4K at 240Hz or 8K at 60Hz with DSC, HDR
- ❑ As specified in HDMI 2.1a: up to 4K 240Hz or 8K 60Hz with DSC, Gaming VRR, HDR

Minimum System Requirements

- ❑ PCI Express-compliant motherboard with one tri-width x16 graphics slot
- ❑ 850 W or greater system power supply
- ❑ One 16-pin PCIe 12VHPWR or two 8-pin supplementary power connectors
- ❑ Microsoft Windows® 11, Windows® 10 64-bit, Linux 64-bit

Part Number	NED408S019T2-1032A
EAN Code	4710562244205
GPU	RTX 4080 SUPER
CUDA Core	10240
Core Clock	2295 MHz
Boost Clock	2550 MHz
DRAM Type	GDDR6X
DRAM Amount	16 GB
DRAM Interface	256 bits
DRAM Speed	23 Gbps
DRAM Bandwidth	736 GB/s
Board Power	320 W
Output	DP 1.4a x 3 HDMI 2.1a x 1
Bracket	2 slot
Cooler	3.1 slot
Board size	328.9 x 132.9 x 63.4 mm
Box size	426.5 x 213.5 x 103.5 mm
Retail Pack	5 pcs per carton
Box including	<ul style="list-style-type: none"> ➢ GeForce RTX 4080 SUPER ➢ Power Cable ➢ ARGB SYNC Cable

Product Specifications and Features are for reference only and are subject to change without prior notice.